Amendments to the Claims

Please withdraw Claims 1, 3-31, 35, 36, 38, 39, and 41-71 as directed to non-elected species. Please amend Claims 32-34. Please add new Claim 72. The Claim Listing below will replace all prior versions of the claims in the application:

Claim Listing

- 1. (Withdrawn) Optical sheeting comprising microstructures that include polyurea.
- 2. (Canceled)
- 3. (Withdrawn) The sheeting of Claim 1, wherein the optical sheeting includes at least one of cube-corner prisms, open-faced cube-corner prisms, linear prisms, lenticular lenses, cylindrical lenses, moth-eye structures, Fresnel lenses, Fresnel lens arrays, lenslets, surface relief diffusers, diffractive structures, light scattering structures, and fish-eye lens arrays.
- 4. (Withdrawn) The sheeting of Claim 1, where the optical sheeting includes at least one of a dye or a pigment.
- 5. (Withdrawn) The sheeting of Claim 1, wherein the sheeting includes a fluorescent colorant.
- 6. (Withdrawn) The sheeting of Claim 5, wherein the fluorescent colorant includes a xanthene-based fluorescent dye.
- 7. (Withdrawn) The sheeting of Claim 5, wherein the fluorescent colorant includes a dye selected from the group consisting of pyranines, anthraquinones, benzopyrans, thioxanthenes, and perylene imides.

- 8. (Withdrawn) The sheeting of Claim 5, wherein the fluorescent colorant includes a dye selected from a group consisting of fluoresceins, rhodamines, eosines, phloxines, uranines, succineins, sacchareins, rosamines, rhodols, pyranines, anthraquinones, benzopyrans, thioxanthenes, and perylene imides.
- 9. (Withdrawn) The sheeting of Claim 1, wherein the optical sheeting is colored.
- 10. (Withdrawn) The sheeting of Claim 1, wherein the optical sheeting includes polymer having a plurality of microstructures disposed therein.
- 11. (Withdrawn) The sheeting of Claim 1, wherein the optical sheeting includes a plurality of two-sided retroreflective components disposed along a substrate.
- 12. (Withdrawn) The sheeting of Claim 11, wherein the components are dispersed in polyurea.
- 13. (Withdrawn) The sheeting of Claim 1, wherein the optical sheeting is for use in a backlit screen.
- 14. (Withdrawn) The sheeting of Claim 1, wherein the polyurea is an aromatic or aliphatic polyurea.
- 15. (Withdrawn) The sheeting of Claim 1, wherein the polyurea is formed from an isocyanate prepolymer and amine resin.
- 16. (Withdrawn) The sheeting of Claim 15, wherein the polyurea includes a polyfunctional polyol.
- 17. (Withdrawn) The sheeting of Claim 15, wherein the isocyanate prepolymer includes a low aliphatic polyisocyanate resin based on hexamethylene diisocyanate (HDI).

- 18. (Withdrawn) The sheeting of Claim 15, wherein the isocyanate prepolymer includes a low viscosity solvent-free polyfunctional aliphatic polyisocyanate resin based on hexamethylene diisocyanate (HDI).
- 19. (Withdrawn) The sheeting of Claim 15, wherein the amine resin has an amine value of between about 100 and 300.
- 20. (Withdrawn) The sheeting of Claim 15, wherein the polyurea further includes a polyol.
- 21. (Withdrawn) The sheeting of Claim 20, wherein the polyol includes a branched polyether polyol.
- 22. (Withdrawn) The sheeting of Claim 20, wherein the polyol has a hydroxyl number in the range of between about 25 and 400.
- 23. (Withdrawn) The sheeting of Claim 20, wherein the polyol is difunctional.
- 24. (Withdrawn) The sheeting of Claim 1, wherein the sheeting includes one or more light stabilizers.
- 25. (Withdrawn) Optical sheeting that includes optical components disposed on a sheet that includes polyurea.
- 26. (Withdrawn) The optical sheeting of Claim 25, wherein the optical components include at least one of cube-corner prisms, open-faced cube-corner prisms, linear prisms, lenticular lenses, moth-eye structures, lenses, Fresnel lens arrays, lenslets, and fish-eye lens arrays.

- 27. (Withdrawn) The optical sheeting of Claim 25, wherein the optical components include polyurea.
- 28. (Withdrawn) A plurality of retroreflective components that are retroreflective on a first side and on a second side, the components being dispersed in polyurea.
- 29. (Withdrawn) A structure comprising optical components dispersed in a polyurea binder.
- 30. (Withdrawn) The structure of Claim 29, wherein the optical components include two-sided retroreflective cube-corner prisms.
- 31. (Withdrawn) The structure of Claim 30, wherein the cube-corner prisms include open-faced cube-corner prisms.
- 32. (Currently amended) A method for forming a sheet that includes polyurea, comprising: providing a carrier substrate;

forming polyurea solvent-free from a isocyanate prepolymer and amine resin depositing polyurea on the carrier substrate;

allowing the polyurea to at least partially cure to form [[the]] <u>a polyurea</u> sheet that includes polyurea; and

removing the carrier substrate.

- 33. (Currently amended) The method of Claim 32 wherein a sheet that includes polyurea, further includes including applying a second carrier substrate over the polyurea prior to curing.
- 34. (Currently amended) The method of Claim 33, wherein a nip roller is used to control a thickness of the <u>polyurea</u> sheet.
- 35. (Withdrawn) A method for forming polyurea comprising:

- a) preparing a first premix by mixing trifunctional polyol with difunctional isocyanate;
- b) preparing a second premix by mixing polyfunctional isocyanate with difunctional polyol and further mixing in difunctional isocyanate;
- c) mixing the first premix with the second premix to obtain a substantially homogeneous prepolymer mixture;
- d) mixing the substantially homogeneous prepolymer mixture with an amine to form the polyurea; and
- e) forming microstructures from the polyurea.
- 36. (Withdrawn) The material of Claim 35, further comprising forming a sheet or film from the polyurea.
- 37. (Canceled)
- 38. (Withdrawn) A method for forming polyurea comprising:
 - a) preparing a first premix by mixing trifunctional polyol with excess difunctional isocyanate to end cap substantially all hydroxyl groups;
 - b) preparing a second premix by:
 - i. capping polyfunctional isocyanate with difunctional polyol; and
 - ii. end-capping the mixture in step i with excess difunctional isocyanate to convert substantially all hydroxyl groups to isocyanates;
 - c) mixing the first premix with the second premix to obtain a substantially homogeneous prepolymer mixture; and
 - d) mixing the substantially homogeneous prepolymer mixture with an amine resin to form the polyurea; and
 - e) forming optical microstructures from the polyurea.
- 39. (Withdrawn) The method of Claim 38, further comprising forming optical sheeting from the polyurea.

- 40. (Canceled)
- 41. (Withdrawn) The method of Claim 38, further comprising mixing a fluorescent dye into the polyurea.
- 42. (Withdrawn) Optical sheeting including polyurea formed from the method of Claim 38.
- 43. (Withdrawn) A method for forming polyurea sheeting, comprising:

dispensing an amine resin onto a substrate;

dispensing an isocyanate prepolymer onto the substrate;

allowing the amine resin and the isocyanate prepolymer to at least partially diffuse into each other; and

winding up the substrate after the amine resin and isocyanate prepolymer have at least partially reacted and cured to form the polymer sheeting.

- 44. (Withdrawn) The method of Claim 43, wherein the substrate is a first substrate, further comprising applying a second substrate to sandwich the polyurea sheeting between the first substrate and the second substrate.
- 45. (Withdrawn) The method of Claim 44, further comprising preheating at least one of the substrates.
- 46. (Withdrawn) The method of Claim 43, further comprising vibrating the substrate to facilitate diffusion.
- 47. (Withdrawn) The method of Claim 43, further comprising dispensing at least one of a dye, pigment, or fluorescent colorant onto the substrate.
- 48. (Withdrawn) A method for forming polyurea sheeting, comprising:

providing a first substrate having a layer of isocyanate prepolymer thereon; providing a second substrate having a layer of amine resin thereon; and

pressing the layer of isocyanate prepolymer against the layer of amine resin to at least partially mix the isocyanate prepolymer with amine resin to form the polyurea sheeting.

- 49. (Withdrawn) The method of Claim 48, further comprising pressing the layer of isocyanate prepolymer against the amine resin with a nip roller.
- 50. (Withdrawn) The method of Claim 49, further comprising winding up the polyurea sheeting.
- 51. (Withdrawn) The method of Claim 48, further comprising heating at least the isocyanate prepolymer or the amine resin to facilitate mixing thereof.
- 52. (Withdrawn) An optical structure having a microstructured surface on a first side and a microstructured surface on a second side, the structure including polyurea.
- 53. (Withdrawn) The optical structure of Claim 52, wherein the microstructured surface for each side is formed from a thermoplastic.
- 54. (Withdrawn) The optical structure of Claim 52, wherein the structure includes an ultraviolet cured thermoset material.
- 55. (Withdrawn) An optical sheet having at least one microstructured surface formed from polyurea.
- 56. (Withdrawn) A polyurea optical structure comprising a one-component polyurea layer attached to a first side of a two-component polyurea layer.

- 57. (Withdrawn) The structure of Claim 56, further comprising a second one-component polyurea layer attached to a second side of the two-component layer.
- 58. (Withdrawn) The structure of Claim 56, further comprising a microstructured layer attached to at least one of the one-component polyurea layers.
- 59. (Withdrawn) The structure of Claim 56, wherein the two-component polyurea layer includes an isocyanate prepolymer and an amine resin.
- 60. (Withdrawn) The structure of Claim 56, further comprising a layer attached to a second side of the two-component polyurea layer.
- 61. (Withdrawn) The structure of Claim 60, further comprising a one-component polyurea layer attached to the layer attached to the second side of the two-component polyurea layer.
- 62. (Withdrawn) A method for forming a polyurea optical structure, comprising:

 providing a one-component polyurea layer on a carrier substrate;

 providing a two-component polyurea layer on the one-component polyurea layer,

 the two-component polyurea layer contacting the one-component polyurea along a first
 side of the two component polyurea layer;

providing a one-component polyurea layer on a second side of the two-component polyurea layer; and

providing a layer on the one-component polyurea that is provided on the second side of the two-component polyurea layer.

- 63. (Withdrawn) The method of Claim 62, further comprising removing the carrier substrate and forming a microstructured layer on the exposed one-component polyurea layer.
- 64. (Withdrawn) The method of Claim 63, further comprising attaching the structure to a garment.

- 65. (Withdrawn) The method of Claim 63, further comprising removing the layer that is provided on the one-component polyurea provided on the second side of the two-component polyurea layer.
- 66. (Withdrawn) A method for forming a polyurea optical structure, comprising: providing a one-component polyurea layer on a carrier substrate; providing a two-component polyurea layer on the one-component polyurea layer, the two-component polyurea layer contacting the one-component polyurea along a first side of the two-component polyurea layer; and providing a layer on a second side of the two-component polyurea layer.
- 67. (Withdrawn) The method of Claim 66, further comprising removing the carrier substrate attached to the one-component polyurea layer and forming a microstructured layer on the exposed one-component polyurea layer.
- 68. (Withdrawn) The method of Claim 66, further comprising forming a one-component polyurea layer on the layer that is attached to the second side of the two-component polyurea layer.
- 69. (Withdrawn) A polyurea optical structure comprising a two-component polyurea layer attached along a first side of the two-component polyurea layer to a microstructured layer.
- 70. (Withdrawn) The structure of Claim 69, further comprising a layer attached to a second side of the two-component polyurea layer.
- 71. (Withdrawn) The structure of Claim 69, further comprising a one-component polyurea layer disposed between the microstructured layer and the two-component polyurea layer.

72. (New) A method for forming a sheet that includes polyurea, comprising: providing a carrier substrate;

forming polyurea on a carrier substrate from an isocyanate prepolymer and amine resin, wherein the isocyanate prepolymer includes a low viscosity solvent-free polyfunctional aliphatic polyisocyanate resin based on hexamethylene diisocyanate (HDI);

allowing the polyurea to at least partially cure to form a sheet that includes polyurea; and

removing the carrier substrate.